



Features:

- 1/3" SONY CCD
- Min. Illumination: 0.14 Lux@F1.4 (Color), 0.014Lux@F1.4 (B/W)
- Anti-flicker mode
- ICR filter auto switch
- Digital Noise Reduction (DNR)
- 2.8~11mm auto iris lens

1/3" CCD

540 TVL

Backlight
Compensation

Privacy
Zone

OSD

3 Axis
Adjustment

Specification:

| | | |
|--------|------------------------|--|
| Camera | Image Sensor: | 1/3" SONY vertical double density interline CCD |
| | Effective Pixels: | 752(H)x582(V) |
| | Horizontal Resolution: | 540TVL (Color), 600TVL (B/W) |
| | Signal System: | PAL |
| | Min. Illumination: | Color: 0.14Lux @ F1.4, 0.0004Lux @ (F1.4, sensitivity×256) B&W: 0.014Lux @ F1.4, 0.00004Lux @ (F1.4, sensitivity×256) |
| | Electronic Shutter: | 1/50s~1/100,000s |
| | Day& Night: | IR cut filter with auto switch |
| | Wide Dynamic Range: | 160X |
| | Synchronization: | Internal/Power synchronization |
| | Video Output: | 1Vp-p Composite Output (75Ω/BNC); Test Monitor OUT (1Vp-p Composite Output (75Ω/BNC), Device Line) |
| | S/N Ratio: | More than 50dB |
| | Adjustment Range: | Pan 0~355°, Tilt ±80°, Rotation 0~150° |



| | | |
|---------|----------------------|--|
| Lens | Lens: | 2.8~11mm@F1.4 (2.5~6mm optional) |
| | Auto IRIS: | DC Drive |
| Menu | Camera ID: | On/Off (15 letters, adjusted position) |
| | Auto Gain: | Low/Middle/High/Off |
| | D/N Mode: | Auto/Day/Night |
| | Auto White Balance: | Auto trace WB1/Auto trace WB2/Manual/Auto Control |
| | Private Mask: | On/Off,Maximum 8 Zones |
| | Motion Detection: | ON/Off |
| | Anti-flicker: | On/Off |
| | Language: | English/Chinese |
| | Video: | Gama Correction, Digital Zoom, Digital Noise Reduction, POS/NEG, Mirror, Resolution, Sharpness, Y, C, Pixel Correction |
| General | Power Consumption: | 24VAC/20VA ±10%, 12VDC/300mA ±10% |
| | | 4W (10W MAX With ICR Working) |
| | Working Temperature: | -10°C~60°C(14°F~140°F) |
| | Dimension: | Φ115.93×112.7mm(Φ4.56"×4.44") |
| Weight: | 180g(0.40lbs) | |

Specifications are subject to change without notice.

