



Features:

- Linux OS embedded
- TI DaVinci hardware compression
- High resolution video preview: 1280x960 pixels
- H.264 / MPEG-4 dual stream real time video compression in HD720P/4CIF/DCIF/2CIF/CIF/QCIF
- Up to 32 GB SD/SDHC card local storage
- Support IE and client software for network preview

1/3" CCD Dual Stream Day & Night Web Server Vandal Proof IP66

Specification:

Camera	Image Sensor:	1/3" SONY Progressive Scan CCD
	Effective Pixels:	1280(H)x960(V), 1.3M CCD
	Minimum Illumination:	0.1Lux @ F1.2 (Color) 0.01Lux @ F1.2 (B/W) 0 Lux w/ IR on
	Lens:	2.7-9mm @ F1.2 /Auto Iris lens
	Day& Night:	ICR
Compression Standard	Video Compression:	H.264/MPEG-4(Optional)
	Video Bit Rate:	32 Kbps~8Mbps
	Audio Compression:	OggVorbis
Image	Max Image Resolution:	1280x960
	Frame Rate:	50Hz:12.5fps(1280x960),25fps(1280x720) 60Hz:12.5fps(1280x960),24fps(1280x720)



Functions	Motion Detection:	Support
	Dual Stream:	Support
	SD Card Local Recording:	Support
	HeartBeat:	Support
	Password Protection:	Support
	Protocols:	TCP/IP,HTTP,DHCP,DNS,RTP/RTCP, PPPoE (FTP, SMTP, NTP, SNMP optional)
Interface	Audio Input:	1 channel (2.0 ~ 2.4Vp-p, 1KOhm)
	Audio Output:	1 channel (Line level, 600Ohm)
	Communication:	1 RJ45 10M/100M self-adaptive Ethernet port and 1 RS-485 interface
	Alarm Input:	1 channel
	Alarm Output:	1 channel relay output
General	Power Supply:	24V AC±10%/12V DC±10%, or PoE (Power over Ethernet)(-H:24VAC±10%)
	Power Consumption:	5W (10W with ICR working)(25W for "-H"series with ICR working)
	Working Temperature:	-10°C~60°C(14°F~ 140°F) (" -H" series support-40°C~60°C(-40°F~ 140°F))
	Working Humidity:	90% or less
	Impact Protection:	IEC60068-275Eh, 50J; EN50102, exceeding IK10
	Weather Proof:	IP66
	Dimensions:	Φ156×134.5mm(Φ6.14"×5.30")
	Weight:	1400g (3.08 lbs)

Specifications are subject to change without notice.

