



### Features:

- H.264 video compression
- 4CIF real-time recording
- Each channel supports dual stream
- Up to 16-ch synchronous playback
- Up to 4 SATA HDD at 2TB each

4 SATA HDD

4 CIF

H.264

DVD-RW  
Support

USB 2.0

19" Chassis

### Specification:

Model		SDVR-4304	SDVR-4308	SDVR-4316
Video/Audio Input	Video Compression:	H.264		
	PAL/NTSC Adaptive:	Support		
	Video Input:	4-ch	8-ch	16-ch
	Video Input Interface:	BNC (1.0 Vp-p, 75Ω)		
	Audio Compression:	OggVorbis		
	Audio Input:	4-ch		
	Audio Input Interface:	RCA (2.0 Vp-p, 1 kΩ)		
	Voice Talk Input:	1-ch RCA(2.0Vp-p, 1kΩ)		
Video/Audio Output	Preview Resolution:	PAL: 704x576; NTSC: 704x480		
	VGA Output:	1-ch, resolution: 1024x768/60Hz		
	Recording resolution:	4CIF/DCIF/2CIF/CIF/QCIF		
	Video output:	2-ch, BNC(1.0Vp-p, 75Ω)		
	Video Spot Output:	1-ch, BNC(1.0Vp-p, 75Ω)		
	Video Loop Output:	4-ch, DB15		
	Frame Rate:	PAL: 1/16-25fps, NTSC:1/16-30fps		
	Video Bit Rate:	32Kbps~2048Kbps, or user-defined		
	Stream Type:	Video/Video&Audio		
	Audio Output:	1-ch RCA(Linear electrical level, 600Ω)		
	Audio Bit Rate:	16kbps		
	Synchronous Playback:	4-ch	8-ch	16-ch
	Dual Stream:	Support		



Hard Disk Driver	Interface Type:	4 SATA Interfaces
	Capacity:	Each interface supports up to 2TB capacity
External Interface	Network Interface:	1 RJ45 10M/100M/1000M adaptive Ethernet Interface
	USB Interface:	2 USB2.0 Interface
	Serial Interface:	1RS-485 interface, 1 RS-232 interface, 1 RS-485 keyboard interface
	Alarm Input:	16-ch
	Alarm Output:	4-ch
General	Power Supply:	100~240VAC, 6.3A, 50~60Hz
	Consumption:	≤ 50W(without hard disk or DVD-R/W)
	Working Temperature:	-10°C ~+55°C
	Working Humidity:	10%~90%
	Chassis:	19" standard 1.5U chassis
	Dimension:	70mm(H)×440mm(W)×390mm(D)
	Weight:	≤ 8Kg(without hard disk or DVD-R/W)

Specifications are subject to change without notice.

