



Features:

- Connection to IP camera, IP dome and video server
- Support decoding at H.264, MPEG4 compression standard
- Up to 1280×1024 VGA output resolution
- Up to 1920×1080 HDMI output resolution
- Support high-definition video preview, storage and playback.
- Digital zoom in preview and playback
- Up to 16-ch synchronous playback

8 SATA HDD

HDMI Output

H.264

DVD-RW Support

USB 2.0

19" Chassis

Specification:

Model	SDVR-H8304	SDVR-H8308	SDVR-H8316	
Video/ Audio Input	Video Compression:	H.264		
	Analog Video Input:	4-ch, BNC(1.0Vp-p, 75Ω), PAL/NTSC adaptive	8-ch, BNC(1.0Vp-p, 75Ω), PAL/NTSC adaptive	16-ch, BNC(1.0Vp-p, 75Ω), PAL/NTSC adaptive
	IP Video Input:	4-ch 4CIF/2-ch 720P/1-ch UXGA Real Time, or 2-ch UXGA not Real Time	8-ch 4CIF/4-ch 720P/2-ch UXGA Real Time, or 4-ch UXGA not Real Time	16-ch 4CIF/8-ch 720P/4-ch UXGA Real Time, or 8-ch UXGA not Real Time
	Composited Video Input:	up to 8-ch (Analog video + IP video)		
	Audio Compression:	OggVorbis		
	Audio Input:	4-ch, BNC(2.0Vp-p, 1kΩ)	8-ch, BNC(2.0Vp-p, 1kΩ)	16-ch, BNC(2.0Vp-p, 1kΩ)
	Voice Talk Input:	2-ch, BNC(2.0Vp-p, 1kΩ)		



Model		SDVR-H8304	SDVR-H8308	SDVR-H8316
Hard Disk Driver	Interface Type:	8 SATA interface		
	Capacity:	Each interface supports up to 2TB capacity		
Video/Audio Output	Preview Resolution:	PAL:704x576 NTSC:704x480		
	CVBS Output:	2-ch, BNC(1.0Vp-p, 75Ω)		
	HDMI Output:	1-ch, resolution: 1920x1080/60Hz, 1280x1024/60Hz, 1920x1080/60Hz		
	VGA Output:	1, resolution: 1024x768/60Hz, 1024x768/70Hz, 1280x1024/60Hz		
	Recording Resolution:	UXGA/720P/4CIF/DCIF/2CIF/CIF/QCIF		
	Frame Rate:	PAL: 25fps, NTSC: 30fps		
	Video Bit Rate:	32Kbps~2048Kbps, or user-defined (Max. 6144Kbps)		
	Audio Output:	2-ch, BNC(linear electrical level, 600Ω)		
	Audio Bit Rate:	16kbps		
	Synchronous Playback:	4-ch	8-ch	16-ch
	Dual Streams:	Yes		
External Interface	Network Interface:	1, RJ45 10M/100M/1000M adaptive Ethernet interface		
	Serial Interface:	1 RS-232 interface (for parameters configuration, maintenance , transparent channel); 1 RS-485 interface (for PTZ control); 1 RS-485 keyboard interface (for special keyboard control)		
	USB Interface:	3, USB2.0		
	Alarm Input:	16-ch		
	Alarm Output:	4-ch		



General	Power Supply:	100~240VAC, 6.3A, 50~60Hz
	Consumption:	≤ 70W (without hard disk or DVD-R/W)
	Working Temperature:	-10°C~+55°C(14°F~131°F)
	Working Humidity:	10%~90%
	Chassis:	19" standard 2U chassis
	Dimension:	450(D)×450(W)×95mm(H)(17.72"(D)×17.72"(W)×3.74"(H))
	Weight(Without HDD):	≤ 8000g(17.64lbs)

Specifications are subject to change without notice.

